

AET AET DISPLAYS LIMITED

Data Sheet

Outdoor Fixed LED Display



* Pictures are for reference only, please subject to actual product

Address: 9-10th Floor , 1st Building, E Zone, Guangda We Valley, 4th Keji Road, Songshan Lake High-tech Industrial Development Zone, Dongguan City, Guangdong Province, China
Contact: sales@aetled.com, +86 0769-38820268

Parameter of Outdoor Fixed LED Display

Model	LED Full Color Display	Outdoor 5S
Module Parameter	LED Type	SMD 3-in-1 Common Cathode
	Pixel Pitch (mm)	5.95mm
	Module Resolution (W*H)	42*42
	Module Dimension (mm)	250*250
	Pixel/m2	28,224
	Servicing	Front
	Cabinet Size (W8H*D,mm)	500*500*85/500*1000*85
	Cabinet Resolution(W*H)	84*84
	Cabinet Material	Aluminum
	Weight (KG)	8.5 KG
Optical Parameter	Contrast Ratio	3000:1
	Scan Rate	7
	Brightness (nits)	7500 - 8000
	Viewing Angle (H/V)	165° /160°
Electrical Parameter	Max Power Consumption (W/cabinet)	≤180
	Average Power Consumption (W/cabinet)	≤60
	Input Power Voltage	AC100-220V, 50/60 (Hz)
Processing Parameter	Drive Mode	Constant Current Drive
	Frame Rate (Hz)	50-60
	Refresh Rate (Hz)	7680Hz
Operational Parameter	Colour Depth (bits)	16
	Life span (Hrs)	100,000
	Operating Temp (°C)	- 20 -- +85
	Storage Temp(°C)	-20 -- +90
	Operating/Storage Humidity (RH)	10-90%
	IP Rating	IP65(front) / IP67(rear)
Video Processor	Green Technology	No need for air-conditioning
	Input	SDI, Composite, RGB,HDMI, DVI, VGA
	Output	HDMI, DVI
Certification	CE, ETL, UV, IP, ROHS	

*Product information is subject to change without prior notice.

AET

9-10th Floor , 1st Building, EZone, Guangda We Valley,
4th Keji Road, Songshan Lake High-tech Industrial Development Zone,
Dongguan City, Guangdong Province ,China

0086-769-38820268 www.aetint.com sales@aetled.com